



# LOG SEALANT LS-1

**Keep Your Log Fresh**

LOG SEALANT LS-1 is a elastomeric water based log sealant that protects the ends of green logs and lumber from checking and splitting. It is a high performance and economical choice for customers. When applied properly to the freshly cut ends, it can prevents log end checking, protecting your logs and extending the life of woods.

- ✔ **Reduce the water loss from log to keep the freshness**
- ✔ **Can be applied to all wood species**
- ✔ **Prevents stain caused by fungi**
- ✔ **Water based, non-toxic formula**

### SURFACE PREPARATION

Log ends or lumber area to be coated must be clear from dirt and debris. Apply LOG SEALANT LS-1 as quickly as possible after end trimming, to achieve the highest level of protection against end checking and degrade.

### APPLICATION

1. Apply LOG SEALANT LS-1 using a brush or roller.
2. Apply as much LOG SEALANT LS-1 as the log or lumber will hold, until it begins to drip slightly.
3. If LOG SEALANT LS-1 does not begin to drip, you may not be applying enough sealer.

### STORAGE

LOG SEALANT LS-1 should be stored in cool and dry place and away from heat. Close the lid tightly after use.

### PACKAGING

20kg

### CLEANING

Use soapy water to clean the equipment. Solvent cleaner are not recommended or needed.

### SPECIFICATIONS

Appearance	: Viscous liquid
Colour	: Yellow (Color can be made upon request)
Solid Content	: 60 % - 70 %
Density	: 0.800 - 0.850 g/ml
Coverage	: 1 - 2 m <sup>2</sup> /kg



Apply the log sealant until it started to drip slightly to make sure that the coating volume is enough.



With LOG SEALANT LS-1



Without LOG SEALANT LS-1