

WOOD PUTTY WP-8

Fix Surface Defect

WOOD PUTTY WP-8 is a ready mixed, general use putty formulated to meet economic and general use for wood industry. It is very easy to apply. Recommended for general use in wood industry, furniture industry, house hold and other related industry. It can be painted, stained or varnished without primming. Suitable for nail holes, crack or split in any timber.

WOOD PUTTY WP-8 possess good performance such as shrinkage, adhesion, hardness and etc.

- ✓ **Easy Application**
- ✓ **Fast Dry Time**
- ✓ **Economical**
- ✓ **Anti shrinkage**
- ✓ **Excellent Durability**

APPLICATION

1. Ensure surfaces are clean, dry and well bound.
2. Apply with stainless steel putty knife, trowel or spatula.
3. Sand with sand paper to smoothen the surface.

STORAGE

Store putty in cool dry place and away from heat. Close the lid tightly after use to avoid putty self-hardening.

PACKAGING

1kg, 1.5kg, 9kg, 30kg and 300kg

SPECIFICATIONS

Appearance	: Semi solid
Colour	: Natural, Oak and Teak (Colour can be formulated based on customer requirement)
Odour	: Odourless
pH @ 30°C	: 7.0 - 10.0
Solid Content	: 75% - 85%
Bulk Density	: 1.5 - 2.5g/ml
Drying Time	: Surface Dry - 5 minutes @ 40°C (Depend on defect) Hard Dry - 30 minutes @ 40°C
Diluting Agent	: Clean Water, maximum up to 2%
Remarks	: The putty is manufactured for ready to use purpose. Do not over dilute with water. This may affect the quality of the product.